

缓冲技术

产品系列概览

工业缓冲器 POWERSTOP	连续运作时每行程最大能量吸收	连续运作时每小时最大能量吸收	急停时每行程最大能量吸收
M4X0.5			
Mini Energy	0.8 J	2100 J/h	0.8 J
M5X0.5			
Mini Energy	0.8 J	2100 J/h	0.8 J
M6X0.5			
Mini Energy	1.8 J	5000 J/h	1.8 J
M8X1.0			
Standard Energy	1.5 J - 4 J	10000 J/h	1.5 J - 5 J
High Energy	1.5 J - 4 J	10000 J/h	1.5 J - 5 J
Adjustable Energy	1.5 J - 4 J	10000 J/h	1.5 J - 5 J
M10X1			
Standard Energy	3 J - 10 J	22000 J/h	3 J - 13 J
High Energy	3 J - 10 J	22000 J/h	3 J - 13 J
Adjustable Energy	3 J - 10 J	22000 J/h	3 J - 13 J
M12X1			
Standard Energy	9 J - 18 J	33000 J/h	9 J - 25 J
High Energy	9 J - 18 J	33000 J/h	9 J - 25 J
Adjustable Energy	9 J - 18 J	33000 J/h	9 J - 25 J
M14X1			
Standard Energy	20 J - 34 J	50000 J/h	20 J - 42 J
High Energy	20 J - 34 J	50000 J/h	20 J - 42 J
Adjustable Energy	20 J - 34 J	50000 J/h	20 J - 42 J
M14X1.5			
Standard Energy	20 J - 34 J	50000 J/h	20 J - 42 J
High Energy	20 J - 34 J	50000 J/h	20 J - 42 J
Adjustable Energy	20 J - 34 J	50000 J/h	20 J - 42 J
M16X1			
Standard Energy	20 J - 34 J	50000 J/h	20 J - 42 J
High Energy	20 J - 34 J	50000 J/h	20 J - 42 J
Adjustable Energy	20 J - 34 J	50000 J/h	20 J - 42 J
M16X1.5			
Standard Energy	20 J - 34 J	50000 J/h	20 J - 42 J
High Energy	20 J - 34 J	50000 J/h	20 J - 42 J
Adjustable Energy	20 J - 34 J	50000 J/h	20 J - 42 J
M20X1.5			
Standard Energy	41 J - 80 J	90000 J/h	41 J - 230 J
High Energy	41 J - 80 J	90000 J/h	41 J - 230 J
Adjustable Energy	41 J - 80 J	90000 J/h	41 J - 230 J
M22X1.5			
Standard Energy	41 J - 80 J	90000 J/h	41 J - 150 J
High Energy	41 J - 80 J	90000 J/h	41 J - 150 J
Adjustable Energy	41 J - 80 J	90000 J/h	41 J - 150 J
M25X1.5			
Standard Energy	105 J - 230 J	120000 J/h	105 J - 400 J
High Energy	105 J - 230 J	120000 J/h	105 J - 400 J
Adjustable Energy	105 J - 230 J	120000 J/h	105 J - 400 J

最小撞击速度	最大撞击速度	最大冲程	重量	UL	CE	UKCA	LABS	REACH	RoHS
0.1 m/s - 0.8 m/s	1.2 m/s - 2.2 m/s	4 mm	0.002 kg				●	●	●
0.1 m/s - 0.8 m/s	1.2 m/s - 2.2 m/s	4 mm	0.003 kg				●	●	●
0.1 m/s - 1.8 m/s	1.2 m/s - 3.5 m/s	5 mm	0.005 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	6 mm	0.01 kg - 0.014 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	6 mm	0.01 kg - 0.014 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	6 mm	0.01 kg - 0.014 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	8 mm	0.017 kg - 0.025 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	8 mm	0.017 kg - 0.025 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	8 mm	0.017 kg - 0.025 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	10 mm	0.028 kg - 0.041 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	10 mm	0.028 kg - 0.041 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	10 mm	0.028 kg - 0.041 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.052 kg - 0.079 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.052 kg - 0.079 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.052 kg - 0.079 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.05 kg - 0.075 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.05 kg - 0.075 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.05 kg - 0.075 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.074 kg - 0.11 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.074 kg - 0.11 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.074 kg - 0.11 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.071 kg - 0.1 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.071 kg - 0.1 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	12 mm - 20 mm	0.071 kg - 0.1 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.11 kg - 0.18 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.11 kg - 0.18 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.11 kg - 0.18 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.15 kg - 0.23 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.15 kg - 0.23 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	15 mm - 25 mm	0.15 kg - 0.23 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.26 kg - 0.43 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.26 kg - 0.43 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.26 kg - 0.43 kg				●	●	●

缓冲技术 产品系列概览

工业缓冲器 POWERSTOP	连续运作时每行程最大能量吸收	连续运作时每小时最大能量吸收	急停时每行程最大能量吸收
M27X1.5			
Standard Energy	105 J - 230 J	120000 J/h	105 J - 400 J
High Energy	105 J - 230 J	120000 J/h	105 J - 400 J
Adjustable Energy	105 J - 230 J	120000 J/h	105 J - 400 J
M27X3.0			
Standard Energy	105 J - 230 J	120000 J/h	105 J - 400 J
High Energy	105 J - 230 J	120000 J/h	105 J - 400 J
Adjustable Energy	105 J - 230 J	120000 J/h	105 J - 400 J
M33X1.5			
Standard Energy	185 J - 400 J	140000 J/h	185 J - 800 J
High Energy	185 J - 400 J	140000 J/h	185 J - 800 J
Adjustable Energy	185 J - 400 J	140000 J/h	185 J - 800 J
M36X1.5			
Standard Energy	185 J - 400 J	140000 J/h	185 J - 800 J
High Energy	185 J - 400 J	140000 J/h	185 J - 800 J
Adjustable Energy	185 J - 400 J	140000 J/h	185 J - 800 J
结构减振器 BASICSTOP	连续运作时每行程最大能量吸收	连续运作时每小时最大能量吸收	急停时每行程最大能量吸收
Axial Standard	0.3 J - 2014 J	9 J/h - 60420 J/h	0.4 J - 2951 J
Axial Advanced	450 J - 12725 J	13500 J/h - 381750 J/h	630 J - 17810 J
Radial Standard	1.2 J - 290 J	36 J/h - 8700 J/h	1.8 J - 427 J
配件			
限位套筒	螺纹		
PAH 系列	M4X0.5 / M5X0.5 / M6X0.5 / M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X3.0 / M33X1.5 / M36X1.5 / M45X1.5		
传感器止动套筒	螺纹		
PSH 系列	M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M20X1.5 / M25X1.5 / M33X1.5 / M45X1.5		
螺栓预支护	螺纹		
PBV 系列	M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X3.0 / M33X1.5 / M36X1.5		
夹持法兰盘正向旋紧	螺纹		
PKS 系列	M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X3.0 / M33X1.5 / M36X1.5 / M45X1.5		
平行拧入的夹紧法兰	螺纹		
PKP 系列	M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X3.0 / M33X1.5 / M36X1.5 / M45X1.5		
锁紧螺母	螺纹		
PVM 系列	M4X0.5 / M5X0.5 / M6X0.5 / M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X1.5 / M27X3.0 / M33X1.5 / M36X1.5 / M42X1.5 / M45X1.5 / M45X2.0 / M64X2.0		
锁紧螺母	螺纹		
PDD 系列	M4X0.5 / M5X0.5 / M6X0.5 / M8X1.0 / M10X1 / M12X1 / M14X1 / M14X1.5 / M16X1 / M16X1.5 / M20X1.5 / M22X1.5 / M25X1.5 / M27X3.0 / M33X1.5 / M36X1.5		
螺钉的	螺纹		
TPC 系列	M2 / M3 / M4 / M5 / M6 / M8 / M12 / M16 / M20		

最小撞击速度	最大撞击速度	最大冲程	重量	UL	CE	UKCA	LABS	REACH	RoHS
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.34 kg - 0.52 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.34 kg - 0.52 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.34 kg - 0.52 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.29 kg - 0.47 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.29 kg - 0.47 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	25 mm - 40 mm	0.29 kg - 0.47 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.55 kg - 0.96 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.55 kg - 0.96 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.55 kg - 0.96 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.71 kg - 1.2 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.71 kg - 1.2 kg				●	●	●
0.1 m/s - 3.0 m/s	1.2 m/s - 5.0 m/s	30 mm - 50 mm	0.71 kg - 1.2 kg				●	●	●
肖式硬度, 硬	肖式硬度, 中等	最大冲程	重量	UL	CE	UKCA	LABS	REACH	RoHS
55D	40D	3 mm - 56 mm	0.001 kg - 0.79 kg				●	●	●
55D	40D	30 mm - 198 mm	0.18 kg - 3.6 kg				●	●	●
55D	40D	15 mm - 60 mm	0.007 kg - 0.3 kg				●	●	●
				UL	CE	UKCA	LABS	REACH	RoHS
			重量				●	●	●
			0.001 kg - 0.56 kg				●	●	●
开关功能			重量				●	●	●
常闭触点 (NC)			0.026 kg - 0.57 kg				●	●	●
防护装置		撞击时最大角度	重量				●	●	●
刮擦器 (NBR) / 无防护装置 / 毡垫圈		30 °	0.016 kg - 0.97 kg				●	●	●
			重量				●	●	●
			0.016 kg - 0.43 kg				●	●	●
			重量				●	●	●
			0.009 kg - 0.2 kg				●	●	●
			重量				●	●	●
			0.001 kg - 0.3 kg				●	●	●
			重量				●	●	●
			0.001 kg - 0.004 kg				●	●	●
钳制扭矩	最大拧入长度 E	扳手开度	重量				●	●	●
0.3 Nm - 185 Nm	2 mm - 20 mm	1.3 mm - 14 mm	0.001 kg - 0.19 kg				●	●	●