

AXIS COMPENSATION MODULES

DGZ2006-16-A

▶ PRODUCT SPECIFICATIONS



▶ Forces and moments

Shows the maximum forces and moments



Mr [Nm]	10
My [Nm]	10
Fa [N]	1150

▶ RECOMMENDED ACCESSORIES



SENSORS



MFS02-S-KHC-P1-PNP

Magnetic field sensor straight, cable 0.3 m - M8 connector



MFS02-S-KHC-P2-PNP

2-point sensor straight, cable 0.3 m - M8 connector



MFS02-S-KHC-IL

Straight position sensor, cable 0.3 m - M8 plug



CONNECTIONS / OTHER



KAG500

Plug-in connector Straight Cable 5m - female connector M8



KAG500B4

Plug-in connector Straight Cable 5m - female connector M8



S8-G-3

Plug-in connector customizable Straight - male connector M8



S8-G-4

Plug-in connector customizable Straight - male connector M8



Order no.	► Technical data
	DGZ2006-16-A
Stroke in Z-axis [mm]	16
Spring force [N]	25 ... 37
Repetition accuracy +/- [mm]	0.01
Operating temperature [°C]	5 ... +80
Certifications	LABS / REACH / RoHS
Protection to IEC 60529	IP54
Weight [kg]	0.55

