


CLAMPING ELEMENTS | HYDRAULIC SERIES DKHS1000

▶ PRODUCT ADVANTAGES



▶ Highest accuracy in rotational axis

No moving functional parts and therefore backlash-free
Drive can be taken out of the drive control

▶ Fastest closing time and pressureless safety function

Due to a low displacement volume and internal stress of the housing

▶ Market leading cycles

Housing strain stays below the elastic fatigue limit

▶ THE BEST PRODUCT FOR YOUR APPLICATION


APPLICATION SCENARIOS

- ▶ Torque take-up of shafts
- ▶ Clamping of torque drive
- ▶ Clamping of C-axis
- ▶ Fixing and safeguarding of swivel bridge
- ▶ Clamping of spindle tilting axis

▶ Technical data

Series	DKHS1000
Shaft diameter	180-460 mm
Holding torque at 1 arcsec	800-6000 Nm
Holding torque at 5 arcsec	1300-8000 Nm
Pressure min. / max.	100 / 110
Spring storage	existing
PLUS connection	No
B10d value	up to 5 million
Dynamic braking cycles	not suitable
Operation	hydraulic
Operating temperature	5 ... +80 [°C]

► BENEFITS IN DETAIL



- ① **Housing**
 - Holding torque due to pre-stressed, high tensile tool steel
- ② **Housing connection**
 - Screw connection to the connecting construction
- ③ **Clamping area**
 - Backlash-free Clamping of the rotary axis
- ④ **Pressure chamber**
 - Opens the element under pressure in the elastic range
- ⑤ **Shaft connection**
 - Connection with the rotary axis
- ⑥ **Sealing**
 - Prestressed and self-enforcing under pressure
- ⑦ **Retain plate**
 - Secures and holds the sealing in position
- ⑧ **Hydraulic connection**
 - Sealing through O-Ring and surrounding cutting ring

► TECHNICAL DATA

► SERIES DKHS1000 HYDRAULIC CLAMPING NC (NORMALLY CLOSED) CLOSED WITHOUT PRESSURE

	Order no.	Shaft Ø [mm]	Holding torque		B [mm]	ØD1 [mm]	ØLK1 [mm]	ØLK2 [mm]
			at 1 arcsec	at 5 arcsec				
			[Nm]	[Nm]				
	DKHS1180-00-A	180	800	1300	20	308	308	169
	DKHS1200-00-A	200	1000	1600	20	328	328	189
	DKHS1220-00-A	220	1500	1900	20	348	348	209
	DKHS1240-00-A	240	1600	2200	20	368	368	229
	DKHS1260-00-A	260	1800	2600	22	388	388	249
	DKHS1280-00-A	280	2400	3000	22	408	408	269
	DKHS1300-00-A	300	2500	3100	22	428	428	289
	DKHS1320-00-A	320	2800	3900	22	448	448	309
	DKHS1340-00-A	340	3000	4200	22	468	468	329
	DKHS1395-00-A	395	4500	6000	26	523	523	382
	DKHS1460-00-A	460	6000	8000	26	598	598	447

