

INDUSTRIAL SHOCK ABSORBERS POWERSTOP THREAD M27X3

► SERIES

PowerStop®



► Material	Stainless steel	► Organic oil (biodegradable)	HEES
► Permitted temperature range	-10 ... +70 [°C]	- H1-certified	Yes
► Angle of Impact max.	2 [°]	- PWIS-free	Yes
► Max. force at fixed stop	17 [kN]	► RoHS compliant - REACH compliant	Yes
► Lock nut tightening torque		► Max. absolute pressure	
- Standard energy	30 [Nm]	- Standard energy	1 [bar]
- High Energy	60 [Nm]	- High Energy	10 [bar]
- Adjustable Energy	60 [Nm]	- Adjustable Energy	10 [bar]

► TECHNICAL DATA

	Design	Series	Thread	Stroke variant	Stroke max. [mm]	Hardness degree	Impact velocity			Energy absorption max.			Protection	Reset			Head Integrated stop	Version		
							Impact velocity		Continuous operation		Emergency stop operation	Force		Time						
							min.	max.	per stroke	per hour	per stroke	min.		max.	max.					
					[m/s]	[m/s]	[J]	[J/h]	[J]	[N]	[N]	[s]								
STANDARD ENERGY	P	SE	27X30	N	25	H	0,1	1,2	105	120.000	105	D	11	26	0,4	D	x			
							M	0,8	2,2	105	120.000	105	-	-	-	-	-	-	-	-
								S	1,8	3,5	105	120.000	105	F	11	26	0,4	S	x	
									W	3,0	5,0	105	120.000	105	A	11	26	0,4	K	x
HIGH ENERGY	P	HE	27X30	N	25	H	0,1	1,2	230	120.000	400	D	26	45	0,4	D	x			
							M	0,8	2,2	210	120.000	330	-	-	-	-	-	-	-	
								S	1,8	3,5	190	120.000	260	F	26	45	0,4	S	x	
									W	3,0	5,0	170	120.000	190	A	26	45	0,4	K	x
ADJUSTABLE ENERGY	P	AE	27X30	N	25	H	0,1	5,0	230	120.000	230	D	26	45	0,4	D	x			
							M	-	-	-	-	-	-	-	-	-	-	-		
								S	-	-	-	-	-	F	26	45	0,4	S	x	
									W	-	-	-	-	-	A	26	45	0,4	K	x
HIGH ENERGY	P	HE	27X30	L	40	H	0,1	1,2	230	120.000	400	D	26	45	0,6	D	x			
							M	0,8	2,2	210	120.000	330	-	-	-	-	-	-	-	
								S	1,8	3,5	190	120.000	260	F	26	45	0,6	S	x	
									W	3,0	5,0	170	120.000	190	A	26	45	0,6	K	x
ADJUSTABLE ENERGY	P	AE	27X30	L	40	H	0,1	5,0	230	120.000	230	D	26	45	0,6	D	x			
							M	-	-	-	-	-	-	-	-	-	-	-		
								S	-	-	-	-	-	F	26	45	0,6	S	x	
									W	-	-	-	-	-	A	26	45	0,6	K	x

PROTECTION

no protection	Felt ring	Wiper (NBR)
D -A	F -A	A -A
in a clean environment	against dust, chips, ...	against liquid, oil, ...

TECHNICAL DRAWINGS

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	N D -A	N E -A	N S -A	N K -A
STANDARD ENERGY				
HIGH ENERGY				
ADJUSTABLE ENERGY				

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	L D -A	L E -A	L S -A	L K -A
HIGH ENERGY				
ADJUSTABLE ENERGY				










INDUSTRIAL SHOCK ABSORBERS POWERSTOP

THREAD M27X3

ACCESSORIES

Pos.	Order no.	Accessories	Remarks
①	PAH27X30-A	Stop sleeve	Including 1x PVM27X30-A. Industrial shock absorber with bellow excluded.
②	PBV27X30ND-A	Side load adapter standard stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
③	PBV27X30NF-A	Side load adapter standard stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
④	PBV27X30NA-A	Side load adapter standard stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑤	PBV27X30LD-A	Side load adapter long stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑥	PBV27X30LF-A	Side load adapter long stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑦	PBV27X30LA-A	Side load adapter long stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑧	PKS27X30-A	Clamping flange orthogonal screwed	Tightening torque of the screws max. 22 Nm.
⑨	PKP27X30-A	Clamping flange screwed in parallel	Tightening torque of the screws max. 10 Nm.
⑩	PVM27X30-A	Stainless steel locknut	Included with the industrial shock absorber.
⑪	PDD27X30-A	Pressure chamber seal	On request. Recommended fixing with PVM27X30-A. Seal must be in full contact on both sides.



▶ CLASSIFICATION

P HE 27X3 L H A K -A

Design

P Industrial shock absorbers PowerStop

Series

ME Mini Energy

SE Standard Energy

HE High Energy

AE Adjustable Energy

Thread

27 Thread nominal diameter

X

30 Thread pitch (factor 10)

Stroke variant

N Standard stroke

L Long stroke

Hardness degree

H Hard (0.1 - 1.2 m/s; Adjustable Energy: 0.1 - 5 m/s)

M Medium (0.8 - 2.2 m/s)

S Soft (1.8 - 3.5 m/s)

W Supersoft (3 - 5 m/s)

Protection

D no protection

F Felt ring

A Wiper (NBR)

B Bellow (TPE)

Head

D Short piston rod no head

E Long piston rod no head

S with steel head

K with plastic head

Version

-A Versioning from a to z