

SPN ZERO-POINT CLAMPING SYSTEM

SPN112P4 - CLAMPING PLATE


► 4-FOLD



- Compact design with optimized design height
- System assembly with high precision
- Integrated air supply/distribution
- Integrated PLUS connection
- Available with the advanced zero-point clamping system on request
- Variable mounting options

► Technical Data

Order no.	SPN112P4E6SD-B	SPN112P4E4SD-B
Operation mode	Pneumatic	Pneumatic
Holding force max.	4xM10/M12	4xM10/M12
Operating pressure [bar]	6 ... 7	4 ... 7
Pull-in force [kN]	6.0	4.0
Pull-in force with PLUS connection [kN]	4x15	4x10
Operating temperature [°C]	-10 ... +70	-10 ... +70
Rotation prevention	Yes	Yes
PLUS connection	Yes	Yes
Air cleaning	No	No
Piston position sensing	No	No
Contact monitoring	No	No
Material	Tempered stainless steel/steel	Tempered stainless steel/steel
Weight [kg]	38	38



- ① Release
- ② Plus connection
- ⑥ Mounting screw*
- ⑦ Thread bore transport
- ⑧ Sealing cap
- ⑨ T-slot nut*
- ⑩ T-slot nut mounting screw*

*Not included in delivery