


消音器

ZTS 系列

▶ 产品优点



- ▶ 可与多种真空发生器灵活搭配使用
- ▶ 高效节能, 经久耐用

▶ 产品代码


ZTS	18M
系列	固定螺纹

▶ 技术数据

订购编号	▶ 技术数据		
	固定螺纹	重量 [kg]	认证
ZTS-01M	G1" 外螺纹	0.048	LABS / REACH / RoHS
ZTS-12M	G1/2" 外螺纹	0.052	LABS / REACH / RoHS
ZTS-14M	G1/4" 外	0.012	LABS / REACH / RoHS
ZTS-18M	G1/8" 外	0.005	LABS / REACH / RoHS
ZTS-25M	G2 1/2" 外螺纹	0.89	LABS / REACH / RoHS
ZTS-34M	G3/4" 外螺纹	0.052	LABS / REACH / RoHS
ZTS-38M	G3/8" 外	0.013	LABS / REACH / RoHS

► 技术图纸

ZTS



① 固定

型号	G [mm]	L1 [mm]	L2 [mm]	L3 [mm]	L4 [mm]
ZTS-01M	32.5	129	11.4	117.6	39.5
ZTS-12M	20.9	129	11	118	39.5
ZTS-14M	13.1	71.5	8	63.5	24
ZTS-18M	9.7	48	5.7	42.3	16
ZTS-25M	75.2	262	19	243	98
ZTS-34M	24.5	129	11	118	39.5
ZTS-38M	16.5	71.5	8	63.5	24